

MATERIAL SAFETY DATA SHEET

<p>OSHA-Meets 29 CFR 1910.1200 Standards</p> <p>Whiting Systems, Inc.</p> <p>Automated Vehicle Wash Systems Industrial Power Wash Systems</p> <p style="text-align: center;">Est. 1974</p>	<p style="text-align: center;">HMIS HAZARD RATINGS</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">HEALTH</td> <td style="width: 33%;">1</td> <td style="width: 33%;">0 = INSIGNIFICANT</td> <td style="width: 33%;">3 = HIGH</td> </tr> <tr> <td>FLAMMABILITY</td> <td>0</td> <td>1 = SLIGHT</td> <td>4 = EXTREME</td> </tr> <tr> <td>REACTIVITY</td> <td>0</td> <td>2 = MODERATE</td> <td></td> </tr> </table> <p style="text-align: center;">TRANSPORTATION INFORMATION</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td>PROPER SHIPPING NAME</td> <td>Not Regulated</td> <td>REF:</td> <td>N/A</td> </tr> <tr> <td>HAZARD CLASS/PKG GRP</td> <td>Not Regulated</td> <td>LABEL:</td> <td>None required</td> </tr> <tr> <td>IDENTIFICATION NUMBER</td> <td>None</td> <td></td> <td></td> </tr> </table>	HEALTH	1	0 = INSIGNIFICANT	3 = HIGH	FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME	REACTIVITY	0	2 = MODERATE		PROPER SHIPPING NAME	Not Regulated	REF:	N/A	HAZARD CLASS/PKG GRP	Not Regulated	LABEL:	None required	IDENTIFICATION NUMBER	None		
HEALTH	1	0 = INSIGNIFICANT	3 = HIGH																						
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME																						
REACTIVITY	0	2 = MODERATE																							
PROPER SHIPPING NAME	Not Regulated	REF:	N/A																						
HAZARD CLASS/PKG GRP	Not Regulated	LABEL:	None required																						
IDENTIFICATION NUMBER	None																								

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST) SmartWash @ Fomula 60	Page 1 of 2
MANUFACTURER'S NAME Whiting Systems, Inc.	EMERGENCY TELEPHONE NUMBER INFOTRAC (800) 535-5053
ADDRESS 9000 Highway 5 North	TELEPHONE NUMBER FOR INFORMATION (800) 542-9031
CITY, STATE, ZIP CODE Alexander, AR 72002	DATE PREPARED: November 3, 2004 SUPERSEDES: February 26, 1999

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S)	CAS #	% (OPTIONAL)	OSHA PEL		ACGIH TWA		SARA	RQ
			PPM	MG/M3	PPM	MG/M3	TITLE III	LBS
Sodium phosphate, tribasic (STPP) (a)	7758-29-4	1 - 5	Not established					5000
Sodium dodecylbenzene sulfonate (a)	25155-30-0	7 - 13	Not established					1000

(a) The comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24,000 lbs.) or greater amounts, according to 40 CFR 302.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: Breathing concentrated vapors may cause irritation of respiratory tract.	Remove affected person to fresh air; wash mouth and nasal passages with water repeatedly; if breathing difficulties persist seek medical attention.
SKIN: Prolonged contact may cause irritation.	Wash contacted area with soap and water; DO NOT attempt to neutralize with chemical agents; if irritation persists, seek medical attention.
EYES: Contact with eyes will cause irritation.	Check for and remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention immediately.
INGESTION: May cause gastric distress, vomiting and diarrhea.	Drink large quantities of water or milk; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek medical attention immediately.
CARCINOGENICITY NPT? No IARC MONOGRAPHS? No OSHA REGULATED? No	

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT Non-flammable	NFPA RATING None	FLAMMABLE LIMITS LEL: N/A UEL: N/A
EXTINGUISHING MEDIA Carbon dioxide, water, water fog, dry chemical, chemical foam.		
SPECIAL FIRE FIGHTING PROCEDURES Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released. Material is alkaline and will irritate the eyes if product is allowed to directly contact the eyes.		
UNUSUAL FIRE AND EXPLOSION HAZARDS None		

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

SmartWash ® Fomula 60

PAGE 2 of 2

Date: November 3, 2004

SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Material is alkaline and will irritate the eyes if product is allowed to directly contact the eyes. Wash small spills to sanitary sewer. Large spills - confine spill, soak up with approved absorbent, shovel product into approved container for disposal. This is a regulated product, refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements.

SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE)

None required while threshold limits are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

VENTILATION

LOCAL EXHAUST: Required

SPECIAL:

To maintain minimum TWA and STEL levels.

MECHANICAL (GENERAL): Yes

OTHER:

Engineering and work controls as required.

PROTECTIVE GLOVES: Neoprene, butyl or nitrile rubber gloves with cuffs.

EYE PROTECTION: Chemical safety goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Coveralls, apron, or other equipment should be worn to minimize skin contact, safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT:

212° F

SPECIFIC GRAVITY (WATER = 1)

1.014

pH

9.5 - 10.0

SOLUBILITY IN WATER

Complete

VAPOR PRESSURE (MM Hg)

17 mm Hg @ 20 ° C

VAPOR DENSITY (AIR = 1)

> 1

EVAPORATION RATE (WATER = 1)

< 1

% VOLATILE (BY WEIGHT)

85.40%

APPEARANCE AND ODOR

Pink liquid, odorless

SECTION 9 - STABILITY AND REACTIVITY

STABILITY

CONDITIONS TO AVOID: Extreme temperatures.

UNSTABLE:

STABLE: XXX

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong oxidizers, strong acids.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION

CONDITIONS TO AVOID: None

MAY OCCUR:

WILL NOT OCCUR: XXX

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for alkaline materials. Consult your local, state, or Federal Environmental Protection Agency before Disposing of any chemicals.

The information provided in this Material Safety Data Sheet has been obtained from sources believed to be reliable. Whiting Systems, Inc. provides no warranties, either expressed or implied and assumes no responsibility for the accuracy or completeness of the data contained herein. This information is offered for your information, consideration and investigation. You should satisfy yourself that you have all current data relevant to your particular use. Whiting Systems, Inc. knows of no medical condition, other than those noted on this material safety data sheet, which are generally recognized as being aggravated by exposure to this product.